



*You Asked, We Delivered!*

Future Design's DR 5000 offers the best of both worlds, ink cartridge or thermal printing!

The DR 5000 is a circular chart recorder like no other. Programmable alarm options combined with "ease of setup" provide the flexibility required for multiple recording applications. The ink style DR 5000 is the first recorder to "self document" setup configuration and can operate using standard or competitive charts, another first in the industry. Eliminate "multi-vendor" chart inventories while reducing operator confusion. Protect your process with the DR 5000 battery backup option, continuous recording for up to 48 hours in the event of power loss.

The thermal print version offers a single chart inventory for all of your recording needs. "Print your own" chart technology includes real time trend and digital data directly on your historical records. No more confusion when replacing charts. The DR 5000 – the right choice for recording.



DR 5000

DR 5000 CIRCLE CHART RECORDER

- Ink or "Print Your Own" chart style
- No manual required for setup
- No "dip switches" to set during configuration
- Uses standard or competitive charts
- Up to 48 hrs of recording during power loss
- Latching or Non-latching relays
- UL, CUL, CE
- "Self Documents" setup configuration

**\$600.00**  
Single-Channel  
Application  
Complete

**DR 5000 SPECIFICATIONS**

**POWER**

Line Voltage: 110/220VAC, 50/60Hz  
Power Consumption: 15 VA maximum

**INPUT**

Thermocouple (T/C): Type J, K, T, R, B, S,  
RTD: PT 100 ohm RTD (385 curve)  
Linear: 4-20 mA, 1-5 VDC, 0-5 VDC  
Range: Per table in manual  
Common Mode Rejection: > 120dB at 60 Hz  
Cold Junction Accuracy: ± 0.2°C @ 25°C ambient  
Ambient Error: ± 0.01% span/°C from 25°C ambient  
Isolation: inputs share common ground on 2 pen units  
Input Impedance: Linear = 249 ohm/ TC = 470Kohm

**RECORDING**

Chart Size: 10"  
Recording Accuracy: ± 0.5% of span (100 division span)  
Sensor Break: Full scale Pen < 10 seconds  
Chart Speed: Configurable  
Input Filtering: Programmable up to 120 seconds

**PROCESS DISPLAY OPTION**

Red LED, 4 digit, .040"

**OPTIONS**

Relay: DPDT, 1.0 Amps @ 120 VAC resistive  
Relay Program: Process, Band, Non-latching, Latching  
Error Protection: De-energized during sensor break  
Hysteresis: Set at 2 units, activation is safe sided  
Battery Back up:  
Ink Style: Up to 48 hours of recording (optional)  
Thermal Print Style: Maintains real time clock only

**ENVIRONMENTAL AND PHYSICAL**

Operating Temperature: 0 to 60°C  
Storage Temperature: -40 to 65°C  
Humidity: 0-90% RH (non-condensing)  
Vibration: 0.3 to 100Hz @ 0.2g  
Mounting: ± 20 degrees of vertical  
± 10 degrees of horizontal  
Moldings: Fire retardant Noryl w/ acrylic window  
Panel Rating: Nema 3 std(Nema4 option)  
Dimensions: 14.0" (H) x 14.0" (W) x 3.8" (D)  
Panel Cutout: Industry Standard 12.7" x 12.7"  
Weight: 7 pounds maximum

For quality sensors at the very lowest prices, ASK TRASK! [www.traskinstrumentation.com](http://www.traskinstrumentation.com)

414 West Poinsett St., Greer, SC 29650 • Phone (864) 848-3993 • Fax (864) 848-9569 • E-mail: [mtrask@bellsouth.net](mailto:mtrask@bellsouth.net)

**Ordering Information - Enter a number in each box which corresponds to the specifications you want when ordering the DR 5000.**

DR 5000							
<p><b>POWER INPUT</b></p> <p>1: 110/220VAC 50/60 Hz Selectable</p>							
<p><b>RECORDING STYLE</b></p> <p>1: 1 Pen Ink 2: 2 Pen Ink 3: Thermal print recorder *** <i>THERMAL RECORDER IS SINGLE OR DUAL CHANNEL PROGRAMMABLE VIA FRONT KEYPAD</i></p>							
<p><b>OUTPUTS</b></p> <p>0: None 1: 1 Relay, DPDT 1A/120VAC resistive 2: 2 Relay, DPDT 1A/120VAC resistive *</p>							
<p><b>DISPLAY OPTIONS</b></p> <p>0: None 1: LED Process Display</p>							
<p><b>CHART OPTIONS</b></p> <p>1: 10" Counterclockwise Rotation (standard) 2: 10" Clockwise Rotation <i>Thermal recorder is only available with counterclockwise rotation</i></p>							
<p><b>ENCLOSURE OPTIONS</b></p> <p>1: Standard 2: Nema 4 3: Platen Mount</p>							
<p><b>SPECIAL OPTIONS</b></p> <p>0: None 1: Battery Backup**</p>							

\* Not available on single pen ink model.

\*\* 48 hours of continuous recording on ink style recorders.

\*\* Battery back-up for real time clock is standard on thermal units.

Thermal recorder will not operate on battery alone. Use order code 000.

\*\*\* Thermal print recorder is configurable for single or dual channels via the front keypad.

Two programmable inputs are standard on the thermal recorder.

UL\CUL FILE# E232762, E232369

CE

UL Pending on Thermal Units.



See us on the web: [www.traskinstrumentation.com](http://www.traskinstrumentation.com)

414 West Poinsett St., Greer, SC 29650 • Phone (864) 848-3993 • Fax (864) 848-9569 • E-mail: [mtrask@bellsouth.net](mailto:mtrask@bellsouth.net)