


RATED CAPACITY	DIMENSIONS								
	A	B	C	D	E	F	G	H	I
1K-5K	9.25	5.00	5.00	6.25	3.75	4.00	2.75	0.50	0.56
10K-25K	12.00	7.90	8.00	7.50	6.00	8.00	6.00	0.75	0.81
35K	12.00	7.90	8.00	7.50	6.00	8.00	6.00	0.75	0.81
50K	16.25	9.30	12.00	11.50	9.50	9.00	6.50	1.00	0.81
75K	16.25	9.30	12.00	11.50	9.50	9.00	6.50	1.00	0.81
100K-125K	23.50	11.75	14.00	20.00	12.00	10.00	8.00	1.12	1.12

**PERFORMANCE SPECIFICATIONS:**

1. CAPACITIES: 1K, 15K, 2K, 25K, 3K, 5K, 10K, 15K, 20K, 25K, 35K, 50K, 75K, 100K, & 125K LB
2. SAFE OVERLOAD: 150% FS
3. FULL SCALE OUTPUT: 3.00 mV/V
4. EXCITATION VOLTAGE: 10-15V AC/DC
5. LOAD CELL RESISTANCE: 700 OHMS
6. LOAD CELL CABLE:
  - 1K-5K: 4 CONDUCTOR, 50 FT
  - 10K-125K: 4 CONDUCTOR, 50 FT (BRAIDED SHIELD)
7. OPERATING TEMPERATURE RANGE: -20°C - +60°C
8. MATERIAL:
  - LOAD CELL: ALLOY STEEL (NICKEL PLATED) OR STAINLESS STEEL
  - ASSEMBLY: MILD STEEL (NICKEL PLATED) OR STAINLESS STEEL

FOR ENGLISH UNITS  
 DIMENSIONS SHOWN  
 UNLESS OTHERWISE SPECIFIED  
 XXX-4-10  
 REV. 10-1-10  
 PART NUMBER 110



THIS DRAWING  
 IS A THIRD  
 ANGLE PROJECTION