

EXTENDED RANGE PROXIMITY SENSORS

**TRASK**  
INSTRUMENTATION, INC.

EXTRA RANGE  
STARTING  
AT JUST \$25.00

- EXTENDED RANGE SENSORS FOR AUTOMATED MACHINERY
- DOUBLE THE RANGE OF STANDARD SENSORS FOR RELIABLE DETECTION
- TIGHT HYSTERESIS FOR A REPEATABLE SENSING RANGE
- HIGH-TORQUE BARREL IS EXTRA THICK FOR MORE DURABILITY
- WRENCH FLATS AND 4-VIEW LED FOR EASY INSTALLATION
- IDEAL FOR USE IN ALL TYPES OF MACHINES FOR PART DETECTION

[HTMSENSORS.COM](http://HTMSENSORS.COM)



# EXTENDED RANGE PROXIMITY SENSORS SPECIFICATIONS



	M8 PICO	M8 MICRO	M12	M18	M30
SENSING DISTANCE	2 mm	2 mm	4 mm	8 mm	15 mm
OPERATING VOLTAGE			10-30 VDC		
OPERATING TEMPERATURE			-25 °C - +70 °C		
HOUSING MATERIAL	Stainless Steel			Chrome Plated Brass	
<b>PART NUMBERS</b>					
DC 3-wire 10-30 V PNP - Open	OCN1-0802P-ACL3	OCN1-0802P-ARL4	OCN1-1204P-ARL4	OCN1-1808P-ARL4	OCN1-3015P-ARL4
DC 3-wire 10-30 V PNP - Closed	OCN1-0802P-BCL3	OCN1-0802P-BRL4	OCN1-1204P-BRL4	OCN1-1808P-BRL4	OCN1-3015P-BRL4
DC 3-wire 10-30 V NPN - Open	OCN1-0802N-ACL3	OCN1-0802N-ARL4	OCN1-1204N-ARL4	OCN1-1808N-ARL4	OCN1-3015N-ARL4
DC 3-wire 10-30 V NPN - Closed	OCN1-0802N-BCL3	OCN1-0802N-BRL4	OCN1-1204N-BRL4	OCN1-1808N-BRL4	OCN1-3015N-BRL4
DC 2-wire 10-30 V - Open	OCN1-0802C-ACL3	OCN1-0802C-ARL4	OCN1-1204C-ARL4	OCN1-1808C-ARL4	OCN1-3015C-ARL4
DC 2-wire 10-30 V - Closed	OCN1-0802C-BCL3	OCN1-0802C-BRL4	OCN1-1204C-BRL4	OCN1-1808C-BRL4	OCN1-3015C-BRL4

EXTENDED RANGE SENSORS ARE THE BEST VALUE IN THE SENSOR LINE UP WITH GREAT PERFORMANCE FEATURES, EXTENDED RANGE, MORE DURABILITY AND A LOW PRICE FOR ALL APPLICATIONS.

**HTM**  
SENSORS

In Canada: 3419 Mainway, Burlington, ON L7M 1A9  
In the USA: 1889 Maryland Ave., Niagara Falls, NY 14305  
Toll Free: 1-800-644-1756  
service@htmsensors.com

**TRASK**  
INSTRUMENTATION, INC.

414 W. Poinsett Street, Greer, SC 29650  
864-848-3993  
traskInstrumentation.com

