

Rechner "NormLine Sensors"

Nov 3, 2017

Rechner Head Office in Germany has been updating product descriptions. The NormLine models we manufacture will also have new product descriptions. The article # KAXXXX for ordering did not change.

A new NormLine promotional flyer is included with this email.

The following is a breakdown of the **NEW** product description for the DC NormLine sensors.

EX: KAS-70-A13-A-M18-PPO-Y3-1-NL

-80-A14-

-A23-

-A24-

- 35-

-A-

-M30-

-M32-PPO-Y3-1-NL

-Z02-

KAS Capacitive

70 Output NPN/supply voltage DC

80 Output PNP/supply voltage DC

A13 M18 x 1, Cylindrical, Flush

A14 M30 x 1.5, Cylindrical, Flush

A23 M18 x 1, Cylindrical, Non-flush

A24 M30 x 1.5, Cylindrical, Non-flush

35 M32 x 1.5, Cylindrical, Non-flush

A Antivalent (NO + NC)

M18 M18 x 1

M30 M30 x 1.5

M32 M32 x 1.5

PPO Active Surface and housing is polyphenylenoxide

Y3 Flange connector, M12 x 1 (plastic), DC, 4 pin

Z02 2m cable

1 Sensitivity Adjustment - Potentiometer

NL NormLine

Our website will be updated to show the new product description. The article # for ordering is already listed with each sensor.

If you have any questions, please contact us.

Thank you.