


FOR CUSTOMER APPROVAL:
 DATE: _____
 INITIALS: _____



MAX TEMP. @ TIP: 400° F
 MAX TEMP. @ TRANSITION: 400° F

THIS DRAWING IS THE SOLE PROPERTY OF JMS SE, AND MUST BE RETURNED UPON DEMAND. IT MAY NOT BE REPRODUCED NOR THE INFORMATION CONTAINED THEREIN USED WITHOUT THE WRITTEN PERMISSION OF JMS SOUTHEAST INC. JMS SOUTHEAST INCORPORATED CERTIFIES THIS DRAWING IS IN ACCORDANCE WITH JMS SOUTHEAST INCORPORATED ENGINEERING SPECIFICATIONS AND ACCURATELY REPRESENTS THE EQUIPMENT FURNISHED.

1	TUBING, .250" OD, 316
2	JMS POTTING COMPOUND #1
3	BULB, Pt, 100Ω @ 0° C, α = .00385, ±.1%Ω @ 0° C, THIN FILM
4	WIRE, 24 AWG STRANDED, TEFLON W/ SSOB
5	HEAT SHRINK, BLACK, GLUE FILLED

Company Name	TRASK
Drawing No.	19499 REV 00 pg 1 of 1

TOLERANCE TABLE:

PROBE (L): 0-18"	±1/8"
18" - 144"	±1/4"
144" +	-1" / +2"
WIRE (L): ≤ 24"	-1/2" / +1"
> 24"	-1/2" / +2"
PROT. TUBE (P & U):	± 1/16"
FRACTIONAL DIM:	± 1/8"
DECIMAL DIM:	
X.XX	± .010"
X.XXX	± .005"

UNLESS STATED OTHERWISE



Michael J. Trask
 P.O. Box 1778 (29652-1778)
 414 West Poinsett Street
 Greer, SC 29650
 864-848-3993 FX: 864-848-9569
 www.traskinst.com